

## Ernitec Q-series motorized zoom lenses



The wide range of Ernitec motorized zoom lenses is designed for durability and reliability.

The Ernitec Q-series consist of a complete range of lenses where a 3-CAM Motor Drive is used. Triple support and guidance of the zoom, focus and iris ensures a very smooth, silent and reliable remote operation.

The Ernitec Q-series deliver excellent optical performance and cover nearly any long distance surveillance in parking lots, highways, airports, border control etc.

- Two years warranty on all Q-series
- Feed-back potentiometer versions.
- Up to 30 times zoom lenses, available in several configurations.
- Megapixel versions available
- 1/2" and 1/3" versions available

Hi Res

Glass optics

Preset

DC iris

Video iris

Spot filter

# Specification

## 1/2 " Lens

Part number	Zoom range	Lens Type	Focal Length mm	Mount Format	Max. Apt.	Filter Thread	Horizontal Angle of View	Min. Obj. Dist. (m)	Time Z/F (sec.)	Dimensions (mm)			Weight
										Dmax	Lmax	H	
0014-02505	10X	<b>Q8Z10SPNA</b>	8-80	C-1/2"	1.8-360	M55x0.75	3.1°-30°	1.2	2.6/4	69	128	80	570g
0014-05455	15X	<b>Q8Z15SAP</b>	8-120	C-1/2"	1.8-360	M55x0.75	2.1°-30°	1.2	3/4	69	128	80	550g
0014-05470	16X	<b>Q8Z16SPNA</b>	8-128	C-1/2"	1.6-360	M55x0.75	1.9°-34°	1.2	3/4	69	128	80	565g
0014-05502	18X	<b>Q11Z18SPNA</b>	11-200	C-1/2"	1.9-360	M72x0.75	1.3°-21.7°	1.5	6/6.5	87	171	80	735g
0015-05552	18X	<b>Q11Z18SAP</b>	11-200	C-1/2"	1.9-360	M72x0.75	1.3°-21.7°	1.5	6/6.5	87	171	80	735g
0014-02505	25X	<b>Q10Z25SPNA</b>	10-250	C-1/2"	1.5-360	-	1.1°-26.3°	2.0	2.5/8.5	122	240.5	122	2300g

## 1/3 " Lens

Part number	Zoom range	Lens Type	Focal Length mm	Mount Format	Max. Apt.	Filter Thread	Horizontal Angle of View	Min. Obj. Dist. (m)	Time Z/F (sec.)	Dimensions (mm)			Weight
										Dmax	Lmax	H	
0014-05353	10X	<b>Q6Z10SAP</b>	6-60	CS-1/3"	1.6-360	M55x0.75	4.7°-44°	1.2	2.6/4	69	114	80	530g
0014-05354	10X	<b>Q6Z10SNA</b>	6-60	CS-1/3"	1.6-360	M55x0.75	4.7°-44°	1.2	2.6/4	69	114	80	530g
0014-05460	15X	<b>Q6Z15SAP</b>	6-90	CS-1/3"	1.6-360	M55x0.75	3.1°-44°	1.2	3/4	69	114	80	550g
0014-05461	15X	<b>Q6Z15SNA</b>	6-90	CS-1/3"	1.6-360	M55x0.75	3.1°-44°	1.2	3/4	69	114	80	550g
0014-05462	15X	<b>Q6Z15SPNA</b>	6-90	CS-1/3"	1.6-360	M55x0.75	3.1°-44°	1.2	3/4	69	114	80	550g
0014-03030	30X	<b>Q5Z30SPNA</b>	5.5-165	CS-1/3"	1.8-360	M72x0.75	1.7°-47.6°	1.8	6/6.5	87	167	80	870g
0014-03060	30X	<b>Q5Z30SNA</b>	5.5-165	CS-1/3"	1.8-360	M72x0.75	1.7°-47.6°	1.8	6/6.5	87	167	80	870g

